



## Model 1700

Rectangular, simple / fixed top, cord brake



Model with anti-swing mechanism (model 1705)



- Design: free-hanging system with cord pull operation (including pendulum safety device/anti-swing mechanism, if chosen)
- Suitability: for vertical rectangular windows
- Installation: in the recess or the glazing bead if deeper than 19mm, on the architrave, the wall or on the ceiling
- Operation: via pull cord with integrated cord brake
- Profile colour: choice of white, silver, bronze or black
- Tensioning: 0.8 mm tension cords, colour-matched to the fabric; number depends on the width of the system.

This pleated blind is mounted on the top rail and stabilised on the bottom rail by tension feet. A pull cord on either side raises the blind to any desired height, thanks to the integrated cord brake. The blind is equipped with a pendulum lock, ensuring it runs parallel to the window even when tilted. In addition to a wide selection of fabrics, you can also choose from various profile colours and mounting options, including glazing beads, wall, ceiling, or clamp brackets for window frames. Please refer to the corresponding measuring instructions.

### Model 1700

- Minimum width: 300 mm
- Minimum height: 200 mm
- Max. width: 2200 mm
- Max. height: 3000 mm
- Maximum area: 5.7m<sup>2</sup>
- Max inclination 15°

### Model 1705

- Minimum width: 300 mm
- Minimum height: 200 mm
- Max. width: 2970 mm
- Max. height: 3000 mm
- Maximum area: 5.7m<sup>2</sup>
- Max inclination 15°